

S1P12A120DDE



1200V / 120A SiC Schottky Diode Module

Features

- Superior Figure of Merit Q_C/I_F
- Zero Reverse Recovery Current / Zero forward recovery
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Low forward voltage
- Isolated back-side

Applications

- EV Fast Chargers
- Switch Mode Power Supplies
- Power Factor Correction
- Free Wheeling Diodes in Inverter Stages
- AC/DC Converters
- Solar Inverter
- Pulse Power

Table 1 Key performance and package parameters

Type **V_{RRM}**

S1P12A120DDE



1200V SiC Schottky Diode Module

Table of contents

Table of contents

Features	1
Applications	1
Table of contents	2
1 Maximum ratings	3
2 Thermal / Packaging characteristics	4
3 Electrical characteristics	5
4 Package drawing	6
Revision history	7
Attention	7

S1P12A120DDE



1200V SiC Schottky Diode Module

1 Maximum ratings

Table 2 Maximum rating ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions	Note	
V_{RRM}	Repetitive Peak Reverse Voltage Per Leg	1200	V			
V_R	DC Peak Reverse Voltage	1200	V			
I_F	Continuous Forward Current (Per Leg)	120	A	$T_c = 100$		
		80				$T_c = 115$
		60				
I_{FRM}	Repetitive Peak Forward Surge Current (Per Leg)	300	A	$T_c = 25$, $t_p = 10\text{ms}$		
I_{FSM}	Non-Repetitive Peak Forward Surge Current (Per Leg)	450	A	$t_p = 10\text{ms}$		
2dt	2dt (Per Leg)	230	A^2s	$t_p = 10\text{ms}$		
dV/dt	Diode Ruggedness (Per Leg)	200	V/ns	$V_R = 0\sim 960\text{V}$		
P_{total}	Power dissipation (Per Leg)	375	W	$T_c = 25$		
T_J, T_{stg}	Operating Junction and storage temperature	-55 to +175				

2 Thermal / Packaging characteristics

Table 3 Thermal and packaging characteristics

Symbol	Description	Min.	Typ.	Max.	Unit	Note
R_{th-JC}	Thermal Resistance, Junction to Case	-	0.4	-		
V_{ISO}	Isolation Test Voltage RMS, f=50Hz, t=1min	2.5	-	-	kV	
Creepage	Terminal to Heatsink Creepage Distance	-	8.5	-	mm	
	Terminal to Terminal Creepage Distance	-	10.5	-	mm	
Clearance	Terminal to Heatsink Clearance	-	6.8	-	mm	
	Terminal to Terminal Clearance	-	4.4	-	mm	
T_{jmax}	Maximum Junction Temperature	-	175	-		
T_{jop}	Operation Junction Temperature	-	-55 to +175	-		
T_{STG}	Storage Temperature Range	-	-55 to +175	-		
W	Weight	-	28.5	-	g	
T_M	Screws to Heatsink Mounting Torque	-	-	1.5	N·m	
T_C	Terminal Connection Torque (M4 *9mm)	-	-	1.3	N·m	

¹ Not subject to production test. Parameter verified by design/characterization.

3 Electrical characteristics

Table 4 SiC SBD characteristics (Per Leg)


Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
V _F	Diode Forward Voltage	-	1.5	1.8	V	I _F = 60A, T _j = 25°C	
		-	1.9	-	V	I _F = 60A, T _j = 175°C	
I _R	Reverse Current	-	2	200		V _R = 1200V, T _j = 25°C	
Q _C	Total Capacitive Charge	-	288	-	nC	V _R = 800V I _F = 60A T _j = 25°C	
C	Total Capacitance	-	4240	-	pF	V _R = 0V T _j f = 1MHZ	
		-	208	-		V _R = 400V T _j f = 1MHZ	
		-	152	-		V _R = 800V T _j f = 1MHZ	

S1P12A120DDE



1200V SiC Schottky Diode Module

4 Package drawing



DiM	Millimeter	
	Min	Max
A	33.40	34.60
B	7.25	8.10
C	4.25	4.40
D	4.25	4.40
E	4.15	4.30
F	14.50	15.40
G	30.10	30.20
H	38.00	38.40
I	23.80	24.20
J	11.80	12.20
K	9.40	9.60
L	0.75	0.85
M	12.40	12.80
N	24.50	25.40
O	1.90	2.10
P	3.00	3.80
Q	26.60	27.00
R	3.80	4.20
S	5.10	5.40

Revision history

Document version	Date of release	Description of changes	
V01_00	2024-06-06		

Attention

1. Rohs compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/ EC (RoHS2), as implemented January 2, 2013.

2. REACH compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Sichain representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

3. With respect to information regarding the application of the product, Sichain hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

4.

S1P12A120DDE



7. Except as otherwise explicitly approved by Sichain in a written document signed by authorized representatives of Sichain, Sichain' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

8. For use of our products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a Sichain representatives, for example but not limited to: transportation equipment, primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, and power transmission systems.